

6" Hospitality Hybrid Sleeper Mattress

Hospitality Use



MATTRESS SPECIFICATIONS

SPRING	312 3/4 13 1/2 GAUGE BONNELL UNIT. HEAT TEMPERED FOR STRENGTH AND DURABILITY.
INSULATORS	A .75 OZ POLYESTER INSULATOR IS STAPLED TO THE TOP AND BOTTOM OF THE SPRING.
QUILTING	A 1 OZ LAYER OF LOW MELT FIBER IS MULTI-NEEDLE QUILTED TO DAMASK TICKING FOR COMFORT. A .75 OZ POLYESTER FIBER IS QUILTED IN THE MATCHING BORDER.
TOPPER	A 1.25 OZ VISCO GEL TOPPER FOR ADDITIONAL COMFORT
FABRIC	45% POLYESTER, 55% POLYPROPYLENE DAMASK — WHITE
BOTTOM	14 GAUGE COLOR COORDINATED STITCH BOND FILLER PANEL
BINDING TAPE	A 1 1/4" POLYESTER BINDING TAPE IS SEWN TO TOP AND BOTTOM OF MATTRESS.
CONSTRUCTION	THE INSULATORS ARE STAPLED ON TOP AND BOTTOM OF SPRING UNIT. THE 1.25 VISCO GEL PAD IS APPLIED ON TOP OF INSULATOR. THE DAMASK COVER IS THEN PLACED OVER THE SPRING UNIT. A MATCHING TOP IS THEN TAPED EDGED WITH 1 1/4" BINDING TAPE.
COIL COUNT	QUEEN 345, FULL 299
PACKAGING	THE FINISHED MATTRESS IS PLACED IN A SEALED 2 MIL PLASTIC TO PREVENT SOILING.

MEETS 16 CFR 1632 AND 16 CFR 1633.



- Visco gel over innerspring 6" premium mattress
- Manufactured in the USA
- Designed for traditional sleeper comfort
- Available in Twin, Twin XL, Full and Queen

Available Mattress Widths

33" x 72" x 5.5"	Twin
36" x 72" x 5.5"	Twin XL
52" x 72" x 5.5"	Full
60" x 72" x 5.5"	Queen

FOR PRODUCT INFORMATION & SALES

Hickory Springs Manufacturing
235 2nd Avenue NW | Hickory NC 28603-0128 | Telephone 828-328-2201

HICKORY SPRINGS

HOSPITALITY

www.hickorysprings.com